



8.2 Thread Rolling Machine-Flat Type



BT Thread Rolling Machine Flat Type - ZR Series

Model	Dia Ø (mm)	Max. Blank Length (mm)	Max. Thread Length (mm)	Die Dimension	Output (pcs/min)	Main Motor (hp)	Net Weight (kg)	Machine Dimensions (L x W x H) (cm)
JBT-ZR5050	3-5	50	50	25X57X90/105	160-210	4	1550	180x150x170
JBT-ZR5075	3-5	75	50	25X82X90/105	160-190	5.5	1600	180x150x170
JBT-ZR5090	3-5	90	50	25X97X90/105	160-190	5.5	1600	180x150x170
JBT-ZR6075	3-6	75	70	25X82X100/115	130-170	5.5	1700	190x150x170
JBT-ZR6090	3-6	90	70	25X97X100/115	130-170	5.5	1750	190x150x170
JBT-ZR60120	3-6	120	70	25X127X100/115	120-160	5.5	1750	190x150x170



KJ Automatic Thread Rolling Machine

Model	Dia Ø (mm)	Max. Screw Length (mm)	Max. Thread Length (mm)	Output (pcs/min)	Main Motor (KW)	Die Pocket Dimension	Net Weight (kg)	Machine Dimensions (L x W x H) (cm)
GCS3A	2-3	30	30	230-270	1.5	25x30x70/80	600	140x80x125
GCS3B	2-3	30	30	230-270	1.5	25x30x70/80	600	140x80x125
GCS4AH45	2.5-4	45	45	180-230	2.2	25x45x75/90	900	140x190x130
GCS4BH45	2.5-4	45	45	180-230	2.2	25x45x75/90	900	140x190x130
GCS4A	3-5	55	55	160-200	3	25x55x85/100	1100	187x121x165
GCS4B	3-5	55	55	160-200	3	25x55x85/100	1100	172x130x150
GCS6AH55	3-6	50	50	120-160	4	25x70x110/125	1400	175x140x140
GCS6BH55	3-6	50	50	120-160	4	25x55x110/125	1400	175x140x130
GCS6BH70	3-6	70	70	120-140	5.5	25x70x110/125	1470	188x142x160
GCS6BG	3-6	85	70	120-140	5.5	25x70x110/125	1470	188x142x160
GCS6BH105	3-6	105	105	100-140	5.5	25x105x110/125	1650	200x160x160
GCS6BH40L	3-8	45	45	60-90	4-P6	40x45x235/260	2500	218x135x140
GCS8BH80	3-8	80	75	90-130	7.5	30x80x150/170	3100	235x170x160
GCS8BH105	4-8	105	105	90-130	7.5	30x105x150/170	3200	235x170x166
GCS8BH150	4-8	150	150	90-110	15-P6	30x150x150/170	3300	245x200x167
GCS12B	6-14	150	150	60-75	15-P6	40x150x190/210	5500	315x196x170